



**Special Application Gauges**  
**Type 1150H, ASME B 40.1 Grade 2A (±0.5% of span)**  
**Type 1122, ASME B 40.1 Grade A (±2-1-2% of span)**

**1150H Reid Vapor Test Gauge**

- Accuracy ASME B 40.1 Grade 2A (±0.5% of span)
- Dial size 4½" only
- White dial and black pointer

**1122KE/KF**

- Accuracy ASME B 40.1 Grade A (±2-1-2% of span)
- Dial size 2½" only

The Ashcroft® Type 1150H is a specialized pressure gauge used by the petroleum industry to measure vapor pressures of various petroleum products.

The Ashcroft® Type 1122 is a specialized product used for some pump, turbine and compressor applications.



**SPECIFICATIONS**

Gauge Type Number	Dial Size (Inches)	Case & Ring Material Finish	Bourdon Tube & Tip Material (all joints welded)	Socket Material	Pressure Range (psi)	Pointer	Movement	NPT Conn.
Reid Vapor Test 1150H	4½"	Case: Aluminum Ring: Threaded Aluminum black epoxy coated	Phosphor Bronze Tip: Brass (All joints silver brazed)	Brass	15/600	Micrometer Adjustable	Stainless steel Teflon coated, pinion and sector shaft, rotary geared	¼"
1122KE(1) 1122KF	2½"	Case: Stainless steel Ring: Bayonet Lock, St.St. Both polished	Phosphor Bronze Tip: Brass (All joints silver brazed)	Brass	15/1000	Non adjustable	Stainless steel	¼"

TYPE 1150H			
Range		Dial Graduations	
kg/cm <sup>2</sup> kilograms per sq. cm.	bar	Figure Interval	Minor Graduation
0/1	0/1	0.1	0.01
0/1.6	1.6	0.2	0.02
0/2.5	2.5	0.5	0.05
0/4	0/4	0.5	0.05
0/6	0/6	0.5	0.1
0/10	0/10	1	0.1
0/16	0/16	2	0.2
0/25	0/25	5	0.5
0/40	0/40	5	0.5

  

Dial Graduations		
Range	Figure Interval	Minor Graduation
kPa (kilopascal)		
0/100	10	1
0/160	20	2
0/250	50	5
0/400	50	5
0/600	50	10
0/1000	100	10
0/1600	200	20
0/2500	500	50
0/4000	500	50

TYPE 1122			
Range		Dial Graduations	
kg/cm <sup>2</sup> kilograms per sq. cm.	bar	Figure Interval	Minor Graduation
0/1	0/1	0.1	0.01
0/1.6	0/1.6	0.2	0.02
0/2.5	0/2.5	0.5	0.05
0/4	0/4	0.5	0.05
0/6	0/6	0.5	0.1
0/10	0/10	1	0.1
0/16	0/16	2	0.2
0/25	0/25	5	0.5
0/40	0/40	5	0.5
0/60	0/60	5	1

  

Compound			
Range	Figure Interval	Minor Graduation	Dual-Scale psi
-1/0/1.5	-1/0/1.5	.5	.05
-1/0/3	-1/0/3	.5	.05
-1/0/5	-1/0/5	.5	.1

  

Compound			
Range	Figure Interval	Minor Graduation	Dual-Scale psi
0/100	10	1	0/14
0/160	20	2	0/22
0/250	50	5	0/35
0/400	50	5	0/55
0/600	50	10	0/85
0/1000	100	10	0/140
0/1600	200	20	0/220
0/2500	500	50	0/350
0/4000	500	50	0/550
0/6000	500	100	0/850

  

Compound			
Range	Figure Interval	Minor Graduation	Dual-Scale psi
-100/0/300	50	5	30"Hg/40
-100/0/500	50	50	30"Hg/70

STANDARD RANGES		
Range psi	Figure Interval	Minor Graduation
<b>Type 1150H</b>		
0/15	1	0.1
0/30	2	0.2
0/45	3	0.2
0/60	4	0.25
0/100	5	0.5
0/200	10	1
0/250	10	1
0/300	10	1
0/600	20	2
<b>Type 1122 (60° dial arc except 15psi-45°)</b>		
0/15	5	1
0/30	10	2
0/60	15	5
0/100	20	10
0/160	40	10
0/200	50	10
0/300	100	25
0/400	100	25
0/600	150	50
0/1000	250	50

(1) The 1122KE is stem mounted.  
 The 1122KF is surface mounted with a front flange.

**TO ORDER THESE 1150H & 1122 GAUGES:**

Select: \_\_\_\_\_ 45 \_\_\_\_\_ 1150 \_\_\_\_\_ H \_\_\_\_\_ 02L \_\_\_\_\_ XXX \_\_\_\_\_ 600#

1. Dial size—2½", 4½" \_\_\_\_\_

2. Type \_\_\_\_\_

3. Tube and socket material—see chart above \_\_\_\_\_

4. Connection size—¼ (02) \_\_\_\_\_

5. Connection location—Lower (L) only \_\_\_\_\_

6. Optional features—see page 176 \_\_\_\_\_

7. Standard pressure range 600 psi \_\_\_\_\_

Accessories—see pages 233-238

Consult factory for guidance in product selection  
 Phone (203) 385-0217, Fax (203) 385-0602 or  
 visit our web site at [www.ashcroft.com](http://www.ashcroft.com)

